

# EXIDE EKO

Perfect partner for three-wheelers  
& light commercial vehicles



**18-MONTH  
WARRANTY\***

\*For conditions, visit [exidereachout.com](http://exidereachout.com)

INDIA MOVES ON **EXIDE**

# EXIDE EKO

## Presenting the Exide Eko Range of three-wheeler & light commercial vehicle batteries

Eko batteries are specially designed for three-wheeler & light commercial vehicle applications, which require frequent start-stops and ply on rough terrains.

- **Rugged Design:** Special polypropylene container makes the battery strong enough to withstand severe operating conditions and arduous vibrations during service
- **Special Hybrid Alloy System:** Best suited for Indian environment
- **Double Clad Separation:** Unique rib-free separator profile, reinforced with texturised glass mat provides surface support to the active material to improve cycle life and resistance to bumps and vibrations
- **Quick Recharge:** Unique grid design, lower internal resistance and a special paste chemistry enhance re-charging capability of the battery during use
- **Spark Arrestor – Safety Device:** Micro-porous filter disc in vent openings arrest acid fumes and restrict spark propagation inside the battery, enhancing safety
- **Leak-Resistant Design:** Side vented lid reduces chance of electrolyte leakage during handling application and keeps the surface of the battery clean
- **Maintenance-Free:** Requires topping up only once in 6 months. Special alloy ensures low water loss during high temperature operations
- **Ready-to-use:** Batteries delivered factory-charged in ready-to-use conditions

### TECHNICAL SPECIFICATIONS OF EXIDE EKO RANGE OF BATTERIES

BATTERY TYPE	PART NUMBER	(REF) C20 CAPACITY (AH)	MAXIMUM OVERALL DIMENSIONS			NOMINAL FILLED WEIGHT(KG)	ELECTROLYTE VOLUME (LTS)	CHARGING CURRENT (AMPS)	CCA at 18°C as per		BATTERY LAYOUT
			L (MM)	W (MM)	H (MM)				IEC	SAE	
EKO22	FEK0-EKO22	22	197	129	227	9.5	2.5	2.5	195	240	Right layout [Diagram]
EKO40	FEK0-EKO40	35	197	129	227	10.4	2.25	2.5	270	332	Right layout [Diagram]
EKO40L	FEK0-EKO40L	35	197	129	227	10.4	2.25	2.5	270	332	Left layout [Diagram]
EKO60L	FEK0-EKO60L	60	260	173	225	17.5	4.7	4.0	288	360	Left layout [Diagram]

Authorised EXIDE Dealer

This catalogue is issued to provide outline information only and is not deemed to form part of an offer or contract. Our policy is one of continuous improvement and we reserve the right to change details without prior notice.