

**EXIDEcare**

**1800 103 5454**

[www.exidereachout.com](http://www.exidereachout.com)

**FITS EVERY NEED.  
FITS EVERY POCKET.**

**CAR • SUV • LCV  
HCV • TRACTOR**



**24-MONTH  
WARRANTY\***

\*For conditions, visit [exidereachout.com](http://exidereachout.com)

**INDIA MOVES ON EXIDE**

Little Champ is a unique factory-charged, ready-to-use battery. Powered by an Advanced Hybrid Technology, it is best suited for temperatures in India, unlike most other untried entrants in the market. With a rugged design to withstand bumps and vibrations for heavy duty applications, Little Champ gives you that much needed edge on Indian roads.



- Unique features and superior technology: Advanced Hybrid Technology that is best suited to withstand the high temperatures prevalent in India.
- Ready-to-use for all terrains: Factory-charged batteries with a polypropylene body, ensures optimum performance in any weather condition. Corner reinforcement ribs added to the rugged design container, help to withstand bumps and vibrations for heavy-duty applications.
- Corrosion-resistant: Specially designed Radial Positive Grid prevents corrosion, thereby enhancing the life expectancy.
- Vibration-resistant: A dual plate separation (PE + GM) coupled with a rugged design container enables the battery to withstand high vibration and reduces the possibility of premature failure.
- Splash and spill-resistant: Built-in anti-splash guards placed at the top vented lid fitted with coin flush vent plug for all battery types upto 150Ah and dome type special side vented (Omega) cover design fitted with Venturi type chamber cover for 180Ah batteries.
- Enhanced safety: A rugged grid profile ensures good cranking power and endurance. Moreover, effective fume arrestors are placed on the vent plugs to ensure complete safety.
- Easy to handle: Slot in lids for the 32Ah and 35Ah type of batteries, a butterfly handle for 65Ah and 80Ah batteries, a retractable handle for 88Ah and 100Ah batteries and a moulded handle for 130Ah, 150Ah and 180Ah batteries.
- Expanded Negative plate with adequate surface area for automotive types and specially designed Cast Radial Negative Grids with large surface area for CV applications.

### TECHNICAL SPECIFICATIONS OF LITTLE CHAMP RANGE OF AUTOMOTIVE BATTERIES

| BATTERY TYPE | PART NUMBER   | C <sub>20</sub> CAPACITY (AH) (REF) | MAXIMUM OVERALL DIMENSIONS |        |        | NOMINAL FILLED WEIGHT (KG) | ELECTROLYTE VOLUME (LITRES) | CHARGING CURRENT (A) | CCA AT -18°C AS PER |     | ACID LEVEL INDICATOR | BATTERY LAYOUT                      |
|--------------|---------------|-------------------------------------|----------------------------|--------|--------|----------------------------|-----------------------------|----------------------|---------------------|-----|----------------------|-------------------------------------|
|              |               |                                     | L (MM)                     | W (MM) | H (MM) |                            |                             |                      | IEC                 | SAE |                      |                                     |
| EXLC32R      | FLC0-EXLC32R  | 32                                  | 197                        | 129    | 227    | 9.6                        | 2.40                        | 2.50                 | 195                 | 240 | NOT PRESENT          | Right layout<br>+ [ ] [ ] [ ] [ ] + |
| EXLC35R      | FLC0-EXLC35R  | 35                                  | 197                        | 129    | 227    | 10.1                       | 2.25                        | 3.00                 | 225                 | 280 | NOT PRESENT          | Right layout<br>- [ ] [ ] [ ] [ ] + |
| EXLC35L      | FLC0-EXLC35L  | 35                                  | 197                        | 129    | 227    | 10.1                       | 2.25                        | 3.00                 | 225                 | 280 | NOT PRESENT          | Left layout<br>+ [ ] [ ] [ ] [ ] -  |
| EXLC65R      | FLC0-EXLC65R  | 65                                  | 260                        | 173    | 223    | 17.5                       | 4.00                        | 4.50                 | 315                 | 390 | NOT PRESENT          | Right layout<br>- [ ] [ ] [ ] [ ] + |
| EXLC65L      | FLC0-EXLC65L  | 65                                  | 260                        | 173    | 223    | 17.5                       | 4.00                        | 4.50                 | 315                 | 390 | NOT PRESENT          | Left layout<br>+ [ ] [ ] [ ] [ ] -  |
| EXLC80R      | FLC0-EXLC80R  | 80                                  | 305                        | 173    | 223    | 20.8                       | 4.80                        | 5.50                 | 380                 | 475 | NOT PRESENT          | Right layout<br>+ [ ] [ ] [ ] [ ] + |
| EXLC88L      | FLC0-EXLC88L  | 88                                  | 408                        | 176    | 235    | 26.1                       | 7.20                        | 5.50                 | 385                 | 480 | NOT PRESENT          | Left layout<br>+ [ ] [ ] [ ] [ ] -  |
| EXLC100L     | FLC0-EXLC100L | 100                                 | 408                        | 176    | 235    | 27.2                       | 7.00                        | 6.50                 | 415                 | 515 | NOT PRESENT          | Left layout<br>+ [ ] [ ] [ ] [ ] -  |
| EXLC130R     | FLC0-EXLC130R | 130                                 | 505                        | 182    | 257    | 34.5                       | 8.50                        | 9.00                 | 545                 | 700 | NOT PRESENT          | Right layout<br>+ [ ] [ ] [ ] [ ] + |
| EXLC150R     | FLC0-EXLC150R | 150                                 | 508                        | 222    | 257    | 40.9                       | 10.30                       | 9.00                 | 600                 | 750 | NOT PRESENT          | Right layout<br>+ [ ] [ ] [ ] [ ] + |
| EXLC180R     | FLC0-EXLC180R | 180                                 | 521                        | 278    | 270    | 53.2                       | 16.00                       | 13.00                | 750                 | 950 | NOT PRESENT          | Right layout<br>+ [ ] [ ] [ ] [ ] + |



When you return a used battery to any of our authorised dealers, we contribute on your behalf, to UNICEF's Child Environment Programme. It would not only empower the lives of the underprivileged children who are in dire need of water, sanitation and hygiene in schools, your contribution would help save our environment as well. Lead, a major component in your battery, if not handled responsibly, can harm the environment and our health. Return your used battery and make the world a better place.

Authorised Dealer

This catalogue is issued to provide outline information only and is not deemed to form part of an offer or contract. Our policy is one of continuous improvement and we reserve the right to change details without prior notice.