



Presenting Exide EEZY. The latest entrant from Exide with advanced features and cutting-edge design. Powered by the latest technology, it has been developed with years of expertise and experience. Exide EEZY is easy on the pocket and ideal partner for cars.

- Batteries are manufactured by using new Lead-Tin-Calcium Alloy that helps to deliver higher cranking current and longer shelf life.
- Battery made of Punched Plates from rolled sheet provides superior corrosion resistance & electrical conductivity.
- High cranking power to weight ratio ensures high power in smaller footprint area with excellent Vehicle starting ability.
- Less variance in weight compared to Conventional battery improves consistency & Reliability in product performance.
- Duplex Cover design having unique tortuous path & flow-back mechanism, improves Spill-proof Characteristics under arduous vehicle running condition.
- Effective flame arrestors with micro porous filter disc in vent openings to arrest acid fumes and restrict spark propagation inside the battery which enhances safety
- Special self locking Handle design reduces chance of accident due to come out of Handle from battery.
- Low self-discharge ensures the START even after idle for long durations
- Imported separator, reinforced with texturized mat (embedded on Plates), provides surface support to the active material, thereby improving cycle life and also provides lower electrical resistance.
- Magic Eye : For determination of Electrolyte level & state of charge
- Product styling & appearance provides robust structure & sealed look externally.
- Available factory-charged in ready-to-use condition



48 Month Warranty *
(24 FOC + 24 PRO-RATA)
* T&C Apply

Technical Specifications of Exide Eezy Range of Batteries

Battery Nomenclature	Ref C20 Capacity (Ah)	Maximum Overall Dimensions (MM)			Nominal Filled Weight (KG)	Electrolyte Volume (LITRES)	Charging Current (A)	CCA at - 18°C As Per			Acid Level Indicator	Battery Layout
		L	W	H				EN	IEC	SAE		
FEY0-EY34B19R	33	187	127	227	9.6	2.35	2.5	-	192	240	Present	Right Layout - [] +
FEY0-EY34B19L	33	187	127	227	9.6	2.35	2.5	-	192	240	Present	Left Layout + [] -
FEY0-EY105D31L	85	305	173	225	22.5	5	7	-	560	720	Present	Left Layout + [] -
FEY0-EY105D31R	85	305	173	225	22.5	5	7	-	560	720	Present	Right Layout - [] +
FEY0-EY115D31R	90	305	173	225	23.4	4.9	7	-	600	750	Present	Left Layout + [] -
FEY0-EY35R	35	197	129	227	10.5	2.2	3	-	270	332	Present	Right Layout - [] +
FEY0-EY35L	35	197	129	227	10.5	2.2	3	-	270	332	Present	Left Layout + [] -
FEY0-EY700	65	260	173	225	18.2	4.4	5	-	400	490	Present	Right Layout - [] +
FEY0-EY700L	65	260	173	225	18.2	4.4	5	-	400	490	Present	Left Layout + [] -
FEY0-EY80D26R	72	260	173	225	19.4	4.5	6	-	465	600	Present	Right Layout - [] +