

EXIDE EPIQ



- New advanced, special long life corrosion-resistant PENTA ALLOY which enhances corrosion resistance in service
- Double Clad Polyethylene and Glass Mat separation - high reliability and longer life
- Rugged looks with attractive cosmetics
- Easy to use - Batteries delivered factory charged "ready-to-use" condition
- Special paste formulation for Positive & Negative plates - higher life expectancy with superior charge acceptance in service
- Special Omega type cover design fitted with Venturi type chamber cover - excellent spill-resistant characteristics
- Long wet shelf life - no freshening charge required for up to 6 months from date of manufacture



77 Month Warranty *
(42 FOC + 35 PRO-RATA)
*** T&C Apply**

Technical Specifications of Exide Epiq Range of Batteries

Battery Nomenclature	Ref C20 Capacity (Ah)	Maximum Overall Dimensions (MM)			Nominal Filled Weight (KG)	Electrolyte Volume (LITRES)	Charging Current (A)	CCA at -18°C As Per			Acid Level Indicator	Battery Layout
		L	W	H				EN	IEC	SAE		
FEPO-EPIQ35R	35	197	129	227	12.1	2.1	3	-	270	332	PRESENT	Right Layout - ----- +
FEPO-EPIQ35L	35	197	129	227	12.1	2.1	3	-	270	332	PRESENT	Left Layout + ----- -
FEPO-EPIQ35LBH	35	197	137	227	12.1	2.1	3	-	270	332	PRESENT	Left Layout + ----- -
FEPO-EPIQDIN74L	74	278	175	190	20.8	3.8	6	570	-	-	PRESENT	Left Layout + ----- -