



77 Month Warranty *
(42 FOC + 35 PRO-RATA)

* T&C Apply

- New advanced, special long life corrosion-resistant PENTA ALLOY which enhances corrosion resistance in service
- Double Clad Polyethylene and Glass Mat separation - high reliability and longer life
- Rugged looks with attractive cosmetics
- Easy to use - Batteries delivered factory charged "ready-to-use" condition
- Special paste formulation for Positive & Negative plates - higher life expectancy with superior charge acceptance in service
- Special Omega type cover design fitted with Venturi type chamber cover - excellent spill-resistant characteristics
- Long wet shelf life - no freshening charge required for up to 6 months from date of manufacture

Technical Specifications of Exide Epiq Range of Batteries

Battery Nomenclature	Ref C20 Capacity (Ah)	Maximum Overall Dimensions (MM)			Nominal Filled Weight (KG)	Electrolyte Volume (LITRES)	Charging Current (A)	CCA at - 18°C As Per			Acid Level Indicator	Battery Layout
		L	W	H				EN	IEC	SAE		
FEP0-EPIQ35R	35	197	129	227	12.1	2.1	3	-	270	332	PRESENT	Right Layout -□□□□+
FEP0-EPIQ35L	35	197	129	227	12.1	2.1	3	-	270	332	PRESENT	Left Layout +□□□□-
FEP0-EPIQ35LBH	35	197	137	227	12.1	2.1	3	-	270	332	PRESENT	Left Layout +□□□□-
FEP0-EPIQDIN74L	74	278	175	190	20.8	3.8	6	570	-	-	PRESENT	Left Layout +□□□□-