

EXIDE MATRIX



- Maintenance-free batteries with advanced Ca - Ca system
- Long wet shelf life - no freshening charge required for up to 6 months from date of manufacture
- Special paste formulation for positive and negative plates - higher life expectancy with superior charge acceptance in service
- Double-clad polyethylene and glass mat separation - high reliability and longer life
- Special Omega type cover design fitted with Venturi type chamber cover - excellent spill-resistant characteristics
- Attractive cosmetics



72 Month Warranty *
(36 FOC + 36 PRO-RATA)

* T&C Apply

Technical Specifications of Exide Matrix Range of Batteries

Battery Nomenclature	Ref C20 Capacity (Ah)	Maximum Overall Dimensions (MM)			Nominal Filled Weight (KG)	Electrolyte Volume (LITRES)	Charging Current (A)	CCA at -18°C As Per			Acid Level Indicator	Battery Layout
		L	W	H				EN	IEC	SAE		
FMT0-MTRED35R	35	197	129	227	12.1	2.1	3	-	270	332	PRESENT	Right Layout -+-----+
FMT0-MTRED35L	35	197	129	227	12.1	2.1	3	-	270	332	PRESENT	Left Layout +-----
FMT0-MTRED45L	45	238	129	227	15	2.9	3.5	-	330	410	PRESENT	Left Layout +-----
FMT0-MTREDDIN100	100	353	175	190	23.4	5.5	8	850	-	-	PRESENT	Left Layout +-----