

#### COLF CART BATTERY

RIGHT FOR THE GAME

3EV165

3EV200

8C150

8C165

6C225







Capacity C5 Capacity @80 Amps		165Ah upto 5.0V (at 30°C) 132 Ah (min) upto 5.0V (at 30°C)
Voltage		6V
Dry Battery Weight		21 Kgs ± 5%
Charged Battery Weight		30 Kgs ± 5%
Dimension	Height Overall (up to the Terminal Top)	276 ± 3.0mm
	Width	183 ± 2.0mm
	Length	264 ± 2.0mm
Fill in Electrolyte Specific Gravity		1.255 ± 0.005 (at 30°C)
Fill in Electrolyte Volome		2.3 Lts/Cell Energy Density
Final Electrolyte Specific Gravity		1.275 ± 0.005 (at 30°C)
Energy Density		36 ± Wh/Kg (C-5 Rate)

## EXIDE RANGE



Capacity		200 Ah (at C-5 Rate) 160 Ah (DCH @ 80A upto 5.0V @30°C)
Voltage		6V
Dry Battery Weight		24.5 Kgs ± 5%
Charged Battery Weight		32.5 Kgs ± 5%
Dimension	Height Overall (up to the Terminal Top)	276 ± 3.0mm
	Width	183 ± 2.0mm
	Length	264 ± 2.0mm
Fill in Electrolyte Specific Gravity		1.255 ± 0.005 (at 30°C)
Fill in Electrolyte Volome		2 Lts/Cell
Final Electrolyte Specific Gravity		1.275 ± 0.005 (at 30°C)
Energy Density		36 ± Wh/Kg (C-5 Rate)

Capacity		165Ah (at C-20 Rate)	
DESCRIPTION OF THE PERSON OF		124 Ah (at C-5 Rate)	
Voltage		8V	
Dry Battery Weight		24 Kgs ± 5%	
Charged Battery Weight		31 Kgs ± 5%	
000000	Height Overall	296 + 2 0000	
	(up to the Terminal Top)	286 ± 3.0mm	
Dimension	Width	182 ± 2.0mm	
	Length	264 ± 2.0mm	
Fill in Electrolyte Specific Gravity		1.255 ± 0.005 (at 30°C)	
Fill in Electrolyte Volome		1.4 Lts/Cell	
Final Electrolyte Specific Gravity		1.280 ± 0.005 (at 30°C)	
Energy Density		30.0 - 33.0 Wh/Kg (C-5 Rate)	



# SPECIFICATION

Capacity		150Ah (at C-20 Rate) 114 Ah (at C-5 Rate)
Voltage		8V
Dry Battery Weight		23 Kgs ± 5%
Charged Battery Weight		30 Kgs ± 5%
411.0	Height Overall (up to the Terminal Top)	286 ± 3.0mm
Dimension	Width	182 ± 2.0mm
	Length	264 ± 2.0mm
Fill in Electrolyte Specific Gravity		1.255 ± 0.005 (at 30°C)
Fill in Electrolyte Volome		1.5 Lts/Cell Energy Density
Final Electrolyte Specific Gravity		1.280 ± 0.005 (at 30°C)
Energy Density		30.0 - 33.0 Wh/Kg (C-5 Rate)



### GOLF CART BATTERY



Capacity		225Ah (at C-20 Rate)
		171Ah (at C-5 Rate)
Voltage		6V
Dry Battery Weight		24 Kgs ± 5%
Charged Battery Weight		30 Kgs ± 5%
	Height Overall	285 ± 3.0mm
Dimension	(up to the Terminal Top)	285 ± 3.0mm
	Width	182 ± 2.0mm
Diricholori	Length	264 ± 2.0mm
Fill in Electrolyte Specific Gravity		1.255 ± 0.005 (at 30°C)
Fill in Electrolyte Volome		2 Lts/Cell
Final Electrolyte Specific Gravity		1.280 ± 0.005 (at 30°C)
Energy Density		31.0 - 33.0 Wh/Kg (C-5 Rate)

Head Office Kolkata

6A Hatibagan Road, Entally, Kolkata - 700 014, Phone (033) 2286 6158/6159, Fax (033) 2286 6186, E-mail: indlcare@exide.co.in

Ph.: (03224) 252140/145/296/253, Fax: (03224) 252145

R&D Centre Ph.: (033) 1500 5458/5225/5660

**Central Service** Ph.: (033 2580 0113, Fax: (033) 2581 3930 Ahmedabad Ph.: (079) 6510 8207, Fax (079) 2963 0532

Bengaluru Ph.: (080) 4128 3793, Fax (080) 2574 4226

Chandigarh Ph.: (0172) 500 0014

Chennai Ph.: (044) 2250 0725/726 Coimbatore Ph.: (0422) 470 0105, Fax (0422) 222 0858

Ph.: (011) 2362 7095-98

Ph.: (0361) 245 1669 Hyderabad Ph.: (040) 6516 3958 Ph.: (0731) 654 2293

Kochi

Ph.: (0484) 414 9351, 414 9352, Fax (0484) 414 9311 Ph.: (033) 2286 6158/6159, Fax: (033) 2286 6186

Ph.: (0522) 404 1896/1899/491 3709 Mumbai (Fort) Ph.: (022) 2207 2188/89, Fax (022) 2207 8631

Ph.: (020) 3230 4041-45, Fax (020) 2443 0094 Pune

This catalogue is issued to provide outline information only and is not deemed to form part of an offer or contract. Our policy is one of continued improvement and we reserve the right to change details without prior notice.