



Your most dependable companion

GT MINERS' CAP LAMP





Standards Compliance IS: 2596 Weight of complete lamp 2.45 Kg

SPECIFICATION

HEADPIECE AND CABLE

Weight of headpiece 155g ABS Headpiece material Number of bulbs (Optional) 1 (2) Nominal voltage of bulbs 4V Main bulb (krypton) rating 0.75 A 600 hrs Burning life 0.46 A Auxiliary bulb rating 600 hrs Burning life of auxiliary bulb

Resistance of cable 0.1 ohm

Type of cable





Weight of battery Battery case material Battery cover material Nominal battery voltage Capacity of battery

Cell construction

Electrolyte

Fuse rating

Voltage drop over

10 hour discharge

2 Kg

Polycarbonate Stainless steel

12 Ah (nominal) at 1A to 3.7V

1 tubular positive plate

2 flat negative plates

Synthetic absorbent mat plus microporous envelopes

Sulphuric acid fully

charged 1.280 to 1.300

4.2V - 3.8V

3 A continuous



APPROVALS

- Directorate General of Mines Safety (No. 16(16) 88 Gen/2666) Dt. 03/06/91
- 2. Bureau of Indian Standards IS: 5679: 1986 (Licence CM/L-5265566/0416031)